



100W Flat Solar Roof tiles

Flexible crystalline silicon solar cells, packaged in curved glass and polymer composite materials, perfectly integrated with the shape of traditional roof tiles, creating a new green building material.



Cost-Effective

Replace traditional tiles get power generation benefits



System Match

Stable power generation system | System real-time monitoring | Ensure electricity safety



Super Waterproof

Double waterproof design



Fashion and Beauty

Exclusive patented technology | Bent shape | Perfect integration with building



Installation Convenience

Humanized installation | Installation is same with traditional tiles



Anji Technologies Worldwide Energy Group (UK)

FLAT Solar Roof Tiles

Maximum Power(Pmax)	100W
Open Circuit Voltage(Voc)	31.06V
Short Circuit Current(Isc)	4.0A
Maximum Power Voltage(Vmp)	26.46V
Maximum Power Current(Imp)	3.78A
Panel Dimensions	1460*435*21(±1)mm
Material	Monocrystalline Silicon

Colours : Red - Dark Grey - Black - Green



Anji Technologies Worldwide Energy Group (UK)
110 Butterfield, London Luton Airport Area,
LU2 8DL
Tel: +44 (0) 1582 434393
E-mail: admin@anjitek.co.uk
Web: www.anjitek.co.uk

