



25W, Triple Arched solar tile

Flexible crystalline CIGS thin film , packaged in curved glass and polymer composite materials, perfectly integrated with the shape of traditional roof tiles, creating a new green building material.



Cost-Effective

Replace traditional tiles get power generation benefits



System Match

Stable power generation system | System real-time monitoring | Ensure electricity safety



Super Waterproof

Double waterproof design



Fashion and Beauty

Exclusive patented technology | Bent shape | Perfect integration with building



Installation Convenience

Humanized installation | Installation is same with traditional tiles



Anji Technologies Worldwide Energy Group (UK)

Triple Arched Solar Roof Tiles

| | |
|----------------------------|------------------|
| Maximum Power(Pmax) | 25W |
| Open Circuit Voltage(Voc) | 10.3V |
| Short Circuit Current(Isc) | 3.6A |
| Maximum Power Voltage(Vmp) | 8.1V |
| Maximum Power Current(Imp) | 3.09A |
| Panel Dimensions | 721*500*33(±1)mm |
| Material | CIGS Thin Film |

Colours : Red - Green



Anji Technologies Worldwide Energy Group (UK)

110 Butterfield, London Luton Airport Area,
LU2 8DL

Tel: +44 (0) 1582 434393

E-mail: admin@anjitek.co.uk

Web: www.anjitek.co.uk

